

This listing of claims will replace all prior versions and listings of claims in the present application.

### Listing of Claims

1. (Currently amended) A pipe assembly connection comprising:
- a seated connector having on its exterior a first cylinder section contiguous with a first lipped portion, said first lipped portion being contiguous with a second cylinder section and on its interior a third cylinder section cavity coupled directly to a fourth cylinder section cavity wherein said ~~fourth~~ third cylinder section cavity has a smooth inner surface and is present within said first cylinder section and wherein said fourth cylinder cavity has a threaded inner surface and is present within said first lipped portion and said second cylinder section, said third cylinder cavity and said fourth cylinder cavity being of the same diameter;
- a fifth cylinder cavity coupled directly to said fourth cylinder cavity, wherein said fifth cylinder cavity has a smooth inner surface and is present within said second cylinder section and a terminal section, said fourth cylinder cavity being of greater diameter than said fifth cylinder cavity; and ~~said second cylinder section, third cylinder section being of greater diameter than fourth cylinder section, the end of said third cylinder section joined to fourth cylinder section being threaded; and~~
- a base being cylindrical and having a threaded end for threaded connection within said ~~third~~ fourth cylinder section of said seated connector.
2. (Original) The pipe assembly connection of Claim 1 wherein said second cylinder section is contiguous with a second lipped portion;

3. (Currently amended) The pipe assembly connection of Claim 2 wherein said second lipped portion is contiguous with a said terminal section.

4. (Cancelled)

5. (Previously amended) The pipe assembly connection of Claim 3 wherein said first cylinder section is of wider diameter than said second cylinder section.

6. (Original) The pipe assembly of Claim 5 wherein said threaded end of said base is triangularly threaded.

7. (Currently amended) The pipe assembly of Claim 6 5 wherein said threaded end of said base is squarely threaded.

8. (Original) The pipe assembly of Claim 7 wherein the end of said base is beveled.

---

Claims 9-17 (Withdrawn)